

PRODUCT: DYNAMULSION 1005N

TECHNICAL DATA SHEET:

DYNAMULSION 1005N IS A NONIONIC PARAFFIN EMULSION DESIGNED AS AN ADDITIVE SPECIFICALLY FOR THE EXTERIOR WOOD PROTECTION APPLICATIONS. DYNAMULSION 1005N IS MULTIFUNCTIONAL AND PROVIDES SUPERIOR END USE PROPERTIES INCLUDING:

- > BLOCK RESISTANCE
- > WATER RESISTANCE

PROPERTIES	RANGE
APPEARANCE	WHITE LOW VISCOSITY LIQUID
SOLIDS TYPE	PARAFFIN
NVM %	31.5 - 32.5
PH	6.0 - 7.5
VISCOSITY (CPS)	10 - 60

END USE/MARKETS:

> EXTERIOR WOOD COATINGS

STANDARD PACKAGING:

DYNAMULSION 1005N IS PACKAGED IN 55 GAL DRUMS & TOTES

This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.