

PRODUCT: DYNAMULSION 912N

TECHNICAL DATA SHEET:

DYNAMULSION 912N IS A NONIONIC EMULSION OF POLYETHYLENE THAT HAS BEEN SPECIFICALLY DESIGNED FOR GLOSS ENHANCEMENT IN DEMANDING INK AND OVERPRINT VARNISHE APPLICATIONS.

DYNAMULSION 912N IS DESIGNED TO PROVIDE SUPERIOR END OF USE PROPERTIES INCLUDING:

- > SUPERIOR GLOSS
- > WEATHERABILITY
- > BLOCK RESISTANCE
- > SCRATCH RESISTANCE

PROPERTIES	RANGE
APPEARANCE	WHITE LIQUID
SOLIDS TYPE	POLYETHYLENE
NVM %	39.5 - 40.5
PH	5.0 - 8.0
VISCOSITY (CPS)	<300

END USE/MARKETS:

- > INKS
- > OVERPRINT VARNISHES

STANDARD PACKAGING:

DYNAMULSION 912N IS PACKAGED IN 55 GAL DRUMS & TOTES

This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.